



A	B	C	D	E	F	G	H	I	J
REV	DESCRIPTION			DATE		APPROVED			
S0	CREATED DRAWING			2016/08/29		CHENY			



Recommended Panel Cut-Off



P1

#### Detailed Product Description:

Waterproof connector rating is IP67/IP68

Protected from dust and water during immersion,  
resistant to many oils and chemical etc

#### Electrical character

Rating voltage: 250V AC/DC ,

Insulation resistance: >100MΩ

Rating current : 4A

Contact resistance ≤10mΩ

#### Other Specification

Contact PIN: Phosphor Copper with Gold plating.



Coupling nut/screw: Brass with nickel plating

Insulation plastic: PA66+GF

Degree of protection: IP67/IP68

\*ALL MATERIALS ARE RoHS COMPLIANT.

⑨	OR000012	O-Ring VITON $\phi 7.0 * \phi 1.5$ mm	1	PCS
⑧	PL00007	HD PE	3	g
⑦	PL00004	BLACK PVC 105°	10	g
⑥	OR00008	O-Ring GREEN VITON $\phi 13.0 * \phi 2.0$ mm	1	PCS
⑤	N/A	M16 Brass plated ni NUT L*W=4.0*19mm	1	PCS
④	YDWK0215	M12 M Brass plated ni front mount	1	PCS
③	N/A	M12 X Coding 8pin male connector	1	SET
②	CN00222	RJ45 8P8C STRAIGHT ANGLE WITH SHEILD	1	PCS
①	N/A	NO-UL 24AWG HOOK UP WIRE	1	PCS
ITEM	PART NO.	SPECIFICATION	Q'TY	UNIT



P2

△Contact requires customer confirmation  
WIRE LIST

P1	COLOR	P2
1	WHITE/ORANGE	1
2	ORANGE	2
3	WHITE/GREEN	3
4	GREEN	6
7	WHITE/BLUE	5
8	BLUE	4
5	WHITE/BROWN	7
6	BROWN	8



Shenzhen Signal Electronics Co., LTD

TITLE M12 X CODING 8P/M  
TO RJ45/F ADAPTER

SGN NO 120708-10-006

REV.

DWG NO

S0

CUSTOMER

APPROVED BY

DATE

TOLERANCES ARE:

DECIMALES

ANGLES

THIRD ANGLE PROJECTION

PROJECTION

SIZE: A4

UNITS: mm

SCALE:

SHEET: 1 OF 1

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SIGNAL COMPANY.  
ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SIGNAL COMPANY IS PROHIBITED.