



PROJECT NO:
SGNYD1708070-6


REV	DESCRIPTION	DATE	APPROVED
S0	CREATED DRAWING	2017/09/11	CRB



SCALE:3:1
DETAIL A






DETAIL A



Detailed Product Description:
Waterproof connector rating is IP67
They can not be used permanently under water.

Connector Electrical character
Rating voltage:25V-60V DC ,
Insulation resistance: >100MΩ
Rating current :16PIN/7A,3PIN/10A
Contact resistance of connector ≤5mΩ
Mechanical characteristics:
mating / cycle >500 cycle
Operating temperature: -40°C ~ +115°
Design from DIN EN60664 AND DIN EN61984
Cable ODø3mm-ø9.5mm
3PIN: 0.14-1.5mm²
16PIN:0.14-1.0mm²

*ALL MATERIALS ARE RoHS COMPLIANT.



SECTION A-A



Shen Zhen Signal Electronics co.,Ltd

DRAWN BY	DATE
CHECKED BY	DATE
APPROVED BY	DATE

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE
PROPERTY OF SIGNAL COMPANY.
ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN
PERMISSION OF SIGNAL COMPANY IS PROHIBITED.

TITLE M23 19 PIN FEMALE HEAD METAL
ASSEMBLY (M23*1.0)

SGN NO	230019-02-001	REV.
DWG NO		
CUSTOMER		S0

TOLERANCES ARE:	THIRD ANGLE PROJECTION	
DECIMALES	ANGLES	
.x ±0.5	x' ±2.0'	SIZE: A4
.xx ±0.20	.x' ±1.0'	UNITS: mm
SCALE: 1:1	SHEET: 1 OF 1	